

Style That Works Better

& BARRIER FREE

STUDIOTM UNDERCOUNTER SINK

STUDIO™ UNDERCOUNTER SINK

- Rectangular undercounter mount sink
- · Made from vitreous china
- · Front overflow
- Supplied with mounting kit (047194-0070A) and template
- □ 0614.000 Unglazed Rim 540 x 387mm (21-1/4" x 15-1/4")
- ☐ 0614.300 Glazed underside

Bowl size:

464mm (18-1/4") wide 308mm (12-1/8") front to back 171mm (6-3/4") deep

☐ 0618.000 Unglazed Rim 600 x 422mm (23-5/8" x 16-5/8")


☐ 0618.300 Glazed underside

Bowl size:

537mm (21-1/8") wide 356mm (14") front to back 152mm (6") deep

Compliance Certifications - Meets or Exceeds the Following Specifications:

- ASME A112.19.2M for Vitreous China Fixtures
- CAN/CSA B45 series




^{*} See faucet section for additional models available

E

MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES - CHECK LOCAL CODES.


 Countertop 864mm (34") from finished floor. Lavatory installed 102mm (4") from front edge of countertop.
 Countertop thickness to be 25mm (1") maximum.





FITTING	A	В
CENTER-SET	1-1/16 (27mm)	4 (102mm)
SPREAD	1-1/4 (32mm)	8 (203mm)





NOTES

WE RECOMMEND USING BASIN AS A TEMPLATE TO DETERMINE PROPER CONTOUR. CUT COUNTERTOP 38MM (1-1/2") INSIDE BASIN CONTOUR. ★ DIMENSIONS SHOWN FOR LOCATION OF SUPPLIED AND "P" TRAP ARE SUGGESTED.

▼ UNDERCOUNTER MOUNTING KIT SUPPLIED WITH SINK.

▼ UNDERCOUNTER MOUNTING KIT SUPPLIED WITH SINK. FITTINGS NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.

SEALING COMPOUND SUPPLIED BY OTHERS.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is

These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.